THIS DOCUMENT IS A COPY AND IS NOT THE SOURCE DOCUMENT. INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE. THE INFORMATION CONTAINED HEREIN IS COPYRIGHTED BY HAROLD
BECK AND SONS, INC. CHANGES TO THE
DOCUMENT ARE PROHIBITED. CONTACT
A BECK SALES ENGINEER IF A CERTIFIED
DRAWING IS REQUIRED. - "L" DIMENSION ±3/8 [10] _ 6 17/32" [166] _13 1/32"_ [331] _ 1 1/16" [27] _ 3 1/2" ₋ [89] .625±.010 REAR CLEVIS HOLE DIAMETER— _ 3/4"±1/16" [15.875±.254] 11/16"±1/16" $[19 \pm 2]$.625±.010 (SEE TABLE) [15.875±.254] $[17 \pm 2]$ _ 2 17/32" DIA. [64] 2 5/8" [67] _ 1 9/16" [40] 3 13/32" 4 15/32" [114] 7 15/16" 8 3/8" — FRONT CLEVIS HOLE DIAMETER (SEE TABLE) [202] [216] 1" N.P.T. CONDUIT-POWER CONNECTION 3 13/16" _[97] **-** 3/4" [19] 1" N.P.T. CONDUIT-SIGNAL CONNECTION "A" DIMENSION 8 23/32" **FRONT VIEW** - "D" DIMENSION [221]

BEGK

240 VOLT POWER VERSION REAR & PARTIAL LEFT SIDE VIEW



RIGHT SIDE VIEW

"C" DIMENSION

- ALLOW 6" [152] FOR REMOVAL

MAXIMUM DRIVE TRAVEL	CLEVIS EXTENSION	"A" DIM.	"B" DIM.	"C" DIM.	"D" DIM.	"E" DIM.	"L" DIM. FULLY RETRACTED	"L" DIM. FULLY EXTENDED	120 VOLT APPROX. WT. LBS./KGS.	240 VOLT APPROX. WT. LBS./KGS.
8" [203]	1.25 [32]	7 3/32 [180]	۸ 31/32 [177]	15 11/16 [399]	10 [254]	3 17/32 [90]	19 27/32 [505]	27 27/32 [708]	75/34	84/38
8" [203]	3.90 [99]	9 3/4 [247]	4 5/16 [110]	18 11/32 [466]	12 21/32 [322]	6 3/16 [157]	22 1/2 [572]	30 1/2 [775]	75/34	84/38
8" [203]	4.40 [112]	10 1/4 [260]	3 13/16 [97]	18 27/32 [479]	13 5/32 [334]	6 11/16 [170]	23" [584]	31" [787]	75/34	84/38
8" [203]	6.00 [152]	11 27/32 [301]		20 7/16 [519]	14 3/4 [375]	8 9/32 [211]	24 19/32 [625]	32 19/32 [828]	76/34	85/39
8" [203]	7.00 [178]	12 27/32 [326]		21 7/16 [545]	15 3/4 [400]	9 9/32 [236]	25 19/32 [650]	33 19/32 [853]	76/34	85/39
		,	, ,		,	,	, <u> </u>	, ,	,	,
12" [305]	1.25 [32]	7 3/32 [180]	6 31/32 [177]	15 11/16 [399]	10 [254]	3 17/32 [90]	23 27/32 [606]	35 27/32 [910]	77/35	86/39
12" [305]	3.90 [99]	9 3/4 [247]	4 5/16 [110]	18 11/32 [466]	12 21/32 [322]	6 3/16 [157]	26 1/2 [673]	38 1/2 [978]	77/35	86/39
12" [305]	4.40 [112]	10 1/4 [260]	3 13/16 [97]	18 27/32 [479]	13 5/32 [334]	6 11/16 [170]	27" [686]	39" [991]	77/35	86/39
12" [305]	6.00 [152]	11 27/32 [301]	2 7/32 [56]	20 7/16 [519]	14 3/4 [375]	8 9/32 [211]	28 19/32 [726]	40 19/32 [1031]	78/35	87/39
12" [305]	7.00 [178]	12 27/32 [326]	1 7/32 [31]	21 7/16 [545]	15 3/4 [400]	9 9/32 [236]	29 19/32 [752]	41 19/32 [1056]	78/35	87/39
18" [457]	1.25 [32]	7 3/32 [180]	6 31/32 [177]	15 11/16 [399]	10 [254]	3 17/32 [90]	29 27/32 [758]	47 27/32 [1215]	80/36	89/40
18" [457]	3.90 [99]	9 3/4 [247]	4 5/16 [110]	18 11/32 [466]	12 21/32 [322]	6 3/16 [157]	32 1/2 [826]	50 1/2 [1283]	80/36	89/40
18" [457]	4.40 [112]	10 1/4 [260]	3 13/16 [97]	18 27/32 [479]	13 5/32 [334]	6 11/16 [170]	33" [838]	51" [1295]	80/36	89/40
18" [457]	6.00 [152]	11 27/32 [301]	2 7/32 [56]	20 7/16 [519]	14 3/4 [375]	8 9/32 [211]	34 19/32 [879]	52 19/32 [1336]	81/37	90/41
18" [457]	7.00 [178]	12 27/32 [326]	1 7/32 [31]	21 7/16 [545]	15 3/4 [400]	9 9/32 [236]	35 19/32 [904]	53 19/32 [1361]	81/37	90/41

"B" DIMENSION

- ALLOW 2 3/4" [70]

FOR REMOVAL

NOTES:

- 1. ALL DIMENSIONS ARE FOR 120V POWER VERSION UNLESS OTHERWISE SPECIFIED.
- 2. TOLERANCE $\pm 1/4$ [± 6] UNLESS OTHERWISE SPECIFIED.
- 3. ALL DIMENSIONS ARE IN INCHES AND [MM] UNLESS OTHERWISE SPECIFIED. THREADS AND TAPPED HOLES ARE SPECIFIED AS UNIFIED THREAD SIZES ONLY. CONDUIT PIPE THREADS PER AMERICAN NATIONAL STANDARD TAPER PIPE THREADS (N.P.T.)

HAROLD BECK & SONS INC.

NEWTOWN INDUSTRIAL COMMONS NEWTOWN, PENNSYLVANIA 18940 USA

REAR VIEW

OUTLINE DIMENSIONS BECK GROUP 42 DRIVE
W/REAR CLEVIS EXTENSION
42-109

DRAWN: PDY 6/11/13	SCALE: NONE	DRAWING NO:	REV:
CHECKED: CHH 6/13/13	NONE	18-4219-020	-
APPROVED: HHS 6/13/13		SHEET NO. 1 OF 2	

18-4219-020

